

RADAR APPLICATION DATA SHEET

Please fax or e-mail back to FLO-CORP Fax: (330) 331-7172 | E-mail: sales@flo-corp.com

| CUSTOMER INFORMATION | | | | | | | | | | | | | |
|---|------------|--------------------|-------------------------------|--|---|------------|--------------------------------|--------|----------------------|---|--------|--|--|
| Contact | | | | | | Prepa | ared By | | | | | | |
| Company | | | | | | | Date | | | | | | |
| Address | | | | | | | Notes on the Application | | | | | | |
| City | | Sta | State | | | | | | | | | | |
| Zip/Postal Code | | Pho | Phone | | | | | | | | | | |
| E-mail | | Fax | Fax | | | | | | | | | | |
| | | | | | | | | | | | | | |
| VESSEL INFORMATION | | | (Supply sketch when possible) | | | | Sketch attached | | | Please attach photo of mounting position if available | | | |
| Storage Solids | | Storage Liquids | | | Ρ | Process | | | | Reactor | | | |
| Area Safety Class | sification | | | | | | | | | | | | |
| Height | | | Diameter | | | Fillin | | | g Me | Method | | | |
| Тор: | | | Atmosphere: (indicate a | | | | all that apply) Pressur | | | : | | | |
| Flat | | | Foam | | | Stea | Steam Norm | | | | | | |
| Parabolic | | | Dust | | | | osit | Relie | f | | | | |
| Conical | | | Vapor | | | (build-up) | | | | | | | |
| Mounting Connection (specify type) CRITICAL INFORMATION | | | | | | | | | | RMATION | | | |
| Distance to Sidev | | | | | | | | | | | | | |
| Mounting Connec | | mp. (°F) | ·) | | | | | | Nozzle Length (in) | | | | |
| Max. Temp at Electronics (°F) | | | | | | | | | Nozzle Diameter (in) | | | | |
| Stilling Well Diameter (in) | | | | | | | | | | | | | |
| MATERIAL | | | | | | | | | | | | | |
| Material Being Measured: | | | Liquid | | | | | | Solid Liquid Gas | | | | |
| Material Temperature: Normal (°F) Maximum (°F) | | | | | | | | | | | | | |
| Material Surface: | | Flat | | | | Turbulent | | | Agitated Vortex | | | | |
| Dielectric Consta | int: | | · | | | | |] €r < | < 3 | | εr > 3 | | |
| INSTALLATION (indicate all that apply) | | | | | | | | | | | | | |
| Separation | Side | | | | | enter | | | Manhole | | | | |
| Available Voltage: | | | 100 115 | | | 5 200 | | | 2 | 230 VAC | | | |
| Communications: | | | HART | | | | RS485 | | | None | | | |
| FLO-CORP OFFICE U | JSE ONLY | | | | | | | | | | | | |
| Product(s) Recommended: | | | | | | | | | | | | | |

